FIREPRO CENTABUILD

CI/SfB

L
PIPE ACCESSORIES DATASHEET – Mar 14

Product specifications can change. Contact

В

CHRISTCHURCH (03) 379 9364

WWW.firepro.co.nz sales@firepro.co.nz

us to ensure you have our latest datasheet

Α

PIPE ACCESSORIES

(NOT FIRE RATED)

HEAD OFFICE: AUCKLAND (09) 579 0367

Black Tower (Concrete Former/Rocket)

Used where a gap is required in poured concrete floors for later installation of services. Nail the Black Tower to the timber formwork through the plastic casing, then simply pour the concrete.


Black Towers are supplied complete with a clear cap to prevent concrete spilling into the gap.

Two sizes are available (Black Tower Fat & Black Tower Thin).

Pipe Steady

Pipe Steady is used to hold short lengths of PVC pipe vertical when pouring concrete floors. Pipe steady is a Tidy Flange (see below) with holes for nailing it to the timber formwork.


Wide pipe size range available including 150mm nominal internal diameter pipe.



Tidy Flange

Tidy Flanges when placed around PVC pipes through a floor, wall or ceiling conceal ragged hole edges and give a neat, tidy appearance. The plastic flanges fit pipes from 40mm nominal diameter to 150mm nominal diameter.

The white or red flange is easily painted to match colour scheme requirements.



Product Selector

			Dimension	Dimension	Internal Diameter
	Product	Colour	Α	В	of PVC pipe
Product Name	Code		Nominal mm	Nominal mm	Nominal mm
Black Tower (Fat)	TBF164	Black	164	119	N/A
Black Tower (Thin)	TBT180	Black	180	63	N/A
Pipe Steady	TFR161-30	Red	28	161	150
	TFS110-30	Red	28	110	100
	TFS83-30	Red	28	83	80
	TFS69-30	Red	28	69	65
	TFS56-30	Red	28	56	50
	TFS43-30	Red	28	30	40
Tidy Flange	TFW110-20 white	White	20	110	100
	TFW83-20 white	White	20	83	80
	TFW69-20 white	White	20	69	65
	TFW56-20 white	White	20	56	50
	TFW43-20 white	White	20	43	40

NOTE: The technical information and suggestions for use and application presented herein represent the best information available to us and are believed to be reliable. If used beyond the situations detailed on this datasheet we advise confirming their suitability before installation. All dimensions are nominal.